



KOALA ImpactProtector

Protect the load

- ▶ Best possible protection for your goods – no damage due to the inner heel radius of the fork
- ▶ Collision protection in the fork back: preservation of sensitive surfaces
- ▶ Noise reduction
- ▶ Quick mounting – immediately ready for use
- ▶ Two options:
 - KOALA „red“ with two height-adjustable, integrated velcro strips, suitable for long-term application
 - KOALA A „black“ with four integrated round magnets, suitable for short-term alternating use. During non-use simple fixing to the lift truck.
- ▶ Easy attachment on the lift truck (e.g. on the mast) when not in use



KOALA-R: Mounting with adhesive strap (Velcro)



KOALA-R: supplied with 2 velcro straps long and 2 velcro straps short



KOALA-S: Mounting by magnets at the backside



Attach to the lift truck when not in use

Article No.	Description	Dimensions (approx. mm)	Technical characteristics
KOALA-R	ImpactProtector red with adhesive strap (Velcro)	470x100x30	Polyurethane red Shore hardness standard DIN 53505: 60 Shore A Operating temperature -50°C to +100°C
KOALA-S	ImpactProtector black with 4 magnets	430x70x30	Polyurethane black Shore hardness DIN 53505: 63 Shore A Temperature range -50°C to +100°C

The illustrations only represent the basic principles and do not constitute a contractual entitlement.