



KOALA ImpactProtector

Protects the load!



- ▶ Best possible protection for your goods
- ▶ Reduces impact intensity
- ▶ Noise reduction
- ▶ Quick mounting – immediately ready for use
- ▶ Two options:
 - KOALA „red“ with two height-adjustable, integrated velcro strips, suitable for long-term application
 - KOALA „black“ with four integrated round magnets, suitable for short-term alternating use. During non-use simple fixing to the lift truck
- ▶ When not in use: easy attachment on the lift truck (e.g. on the mast)



KOALA-R: Mounting with adhesive strap (Velcro)



KOALA-R: supplied with 2 velcro straps long and 2 velcro straps short



KOALA-S: Mounting by magnets at the backside



Attach to the lift truck when not in use

Article No.	Description	Dimensions (inches)	Technical characteristics
KOALA-R	ImpactProtector red with adhesive strap (Velcro)	18.5 x 4 x 1.2	Polyurethane red Shore hardness standard DIN 53505: 60 Shore A Operating temperature -58°F to +212°F
KOALA-S	ImpactProtector black with 4 magnets	17 x 2.8 x 1.2	Polyurethane black Shore hardness DIN 53505: 63 Shore A Temperature range -58°F to +212°F

The illustrations only represent the basic principles and do not constitute a contractual entitlement.

